

NFD LAMINATE FLOORING INSTALLATION GUIDE

PRODUCTS: 8MM & 12MM UNICLIC CLICK SYSTEM

Please read and follow all instructions below before installation. Please ensure that a dust mask (minimum P2) is used during installation.

Introduction:

NFD Laminate is a floating floor suitable for both domestic and commercial purposes. NFD laminate flooring can be installed over almost any existing floor structure providing it meets the below requirements. It is suitable for indoor use only and away from prolonged periods of unprotected UV sunlight. It is designed to expand and contract and therefore, cannot be fixed at any point and requires a full 10mm expansion around the entire perimeter. NFD allows a single room area of 12 x 12 mt without transition strips. Expansion join must be used for any length or width exceeding 10mts and repeated thereafter. Transition strips must be used in doorways. NFD supplies all matching scotia, expansion, cover and end trims. NFD Laminate must be installed in a controlled environment within the temperature range of 15-27°C.

Pre-Installation Checklist:

Product Checklist:

- ☐ The installer is responsible for inspecting all materials to verify the supplied product is the correct range, colour, batch, quantity, and is free from defects.
- ☐ The installer should verify with the customer to ensure the product's features - such as product, pattern, colour, shade, size, and embossing - meet their expectations. A minimum of 5 boxes should be opened and planks spread out for accurate assessing.
- ☐ Acclimatise planks for a minimum of 4 hours in the installation space, with boxes stacked flat and individually.
- ☐ NFD does not permit mixing batches/dye lots.

Site Checklist:

- ☐ The site temperature should be regulated between 17-27°C for 24 hours before and 48 hours after installation.
- ☐ Extra care should be taken in areas with windows, where direct sunlight can rapidly raise the temperature of the floor above the installation maximum of 27°C and cause 'hot spots'.
- ☐ If such areas are identified, windows should be blacked out for 24 hours before and 48 hours after installation. For guidance on managing direct sunlight exposure after installation, please refer to the NFD WR Laminate Warranty document.
- ☐ Subfloor complies with AS/NZS 1884:2021
- ☐ NFD does not recommend this product in rooms with floor waste.

Installation can begin once all the above checks have been completed and approved. If any issues arise from the above checklists, contact your NFD representative immediately for a quick resolution. By completing the installation, you confirm that all the above conditions have been reviewed and accepted. Complaints and claims regarding clearly identifiable errors or defects will not be accepted after installation.

NFD Laminate is a floating floor system and should have no single furniture item exceeding 200kg.

Installer Responsibility:

Prior to installing, flooring should be inspected, and the installer must determine that the job-site environment and associated subfloor meet or exceed all applicable standards. NFD declines any job failure responsibility resulting from or associated with subfloors, substrates or job-site environmental deficiencies. Construction and material industries recommendations, as well as local statutory codes, must be adhered. It is recommended that the construction and subfloor be flat, dry and structurally sound. Only suitable materials should be used to correct any subfloor defects.

Subfloor Preparation:

All subfloors must be prepared in accordance with AS/NZ 1884:2021 guidelines. This guide provides important steps to assist in the preparation process, but does not replace the AS/NZ 1884:2021 standard or those of a certified flooring contractor.

It is recommended that any existing floor coverings or remnants are uplifted and removed along with any adhesive residues. Existing cushioned vinyl is never a suitable subfloor for the installation of Laminate. This type of existing floor covering must always be uplifted and removed.

Please ensure any material being removed is asbestos-free. If asbestos is possible, please engage with a registered expert in the handling of the project.

The subfloor must be solid, clean, dry, smooth, flat and level as per AS / NZS 1884. The subfloor must be prepared per the guidelines below for your specific type of subfloor.

- ☐ **Solid:** No Loose tiles, boards, panels. There should be no movement when walked upon.
- ☐ **Clean:** Free from all dust, dirt and existing residues.
- ☐ **Dry:** The subfloor must have a relative humidity of 80% or less (AS 1884:2021)
- ☐ **Smooth:** No more than 0.5mm abrupt surface deviation below a 150mm straightedge.
- ☐ **Flat:** Height difference should not exceed 4mm over any 2000mm distance
- ☐ **Level:** No more than 10mm in any room and no more than 20mm over the entire footprint.

NOTE: It is the responsibility of the contractor to ensure the concrete subfloor has a moisture content of 80% or less as stated in the Australian Standards. It is advised a probe test be carried out and recorded for security against a floor failing post installation caused by moisture that was not encountered at the time of installation.

Acoustic underlay with PE membrane or 200uM builders plastic along with an underlay 3mm or less, must be used. All joins must be taped with a water-resistant joining tape. Plastic membrane must be installed 50mm minimum above vertical surfaces

If the subfloor isn't concrete and is raised off the ground with direct exposure to external elements, please ensure the ventilation is compliant to AS1884:2021. If ventilation is not sufficient, the difference between external and internal temperature could be greatly different, causing potential failure of the Laminate flooring.

If the subfloor is not covered in this installation guide, or if you have any questions or concerns, please contact an NFD representative for clarification before proceeding.

Any variation from this document provided by NFD must be in writing before commencing

Types of Subfloors:

Ceramic Tiles (The below tolerances are accepted by NFD for NFD WR Laminate only)

If NFD WR Laminate is installed over ceramic tiles, a few pointers should be noted. Any loose tiles must be secured or removed and filled with a suitable compound. NFD allows for installation over tiles that are within the above smooth, flat and level guides, with the exception of grout lines that have a maximum depth no greater than 4mm or no wider than 5mm. All high spots must be removed by grinding or levelled with a flood coat to comply with the above smooth tolerance. If the grout exceeds either of these tolerances, a screed must be applied to meet the above smooth, flat and level standards.

Timber Flooring

If the hybrid flooring is installed over existing timber flooring, it should also be noted that any loose boards should be secured, any protrusions such as nails, etc. should be removed.

Failure to do so may result in a deficiency of plank performance and/or appearance. Install either Australian Flooring Standard hardboard or structural ply over existing timber flooring to attain the desired and recommended condition of the pre-installation subfloor. Sand and feather finish joins if necessary.

Yellow Tongue/Particle Board

NFD's hybrid flooring can be installed directly over particle board subfloors, provided the subfloor meets the above standards of AS 1884:2021.

Rubber Flooring

NFD recommends the use of acoustic 'PerformancePlus' 3mm rubber cork underlay. The rubber underlay must be installed as per installation instructions, and then a builders plastic must be installed over the rubber before installation of the NFD Laminate flooring. An equivalent underlay can be used providing it is a high-density compound consisting over 650kg/m³.

Painted Surfaces, Vinyl Sheeting & Linoleum

NFD WR Laminate can be installed over most painted floor surfaces. Please ensure that the subfloor meets the above standards of AS 1884:2021

It is recommended that vinyl sheeting or linoleum that all loose/lifted areas be removed and patched with a suitable compound. The above smooth, flat and level guides must be maintained.

DO NOT:

- At any point, attach/fix NFD WR Laminate plank to subfloor
- Do not fix trims to the flooring. They must be fixed to vertical surfaces or subfloor.
- NFD does not permit the use of silicone on this product.
- Do not fix the skirting in such a way that it restricts the expansion and contraction of the Laminate.

It is important to note that any glass windows or openings that encounter direct sunstrike must have a UV-reducing film or window coverings to lower thermal rays and therefore heat.

Heating Systems: Only into the slab, Hydronic Underfloor systems can be used.

1. The surface temperature must not exceed 28°C
2. Use the heating system at maximum capacity to remove any excess moisture before installing.
3. Maintain the room temperature between 15-26°C 24 hours prior to installation.
4. Flooring products must be kept in the same environment for at least 24 hours before use.
5. Apply heat gradually, 24 hours after installation. An increase in temperature must be maintained to less than 2 degrees per 4 hours.

Installation:

1. Prepare all rulers, cutters, spreaders and compass dividers before begin to work.
2. Check that the colour is as selected. Once installed, NFD is not responsible for colour/dye or colour inconsistencies. Check that the boxes of planks are of the same batch/lot number.
3. Find the exact centre of the floor by marking vertical and horizontal lines across the floor.

4. Measure the squareness of the marked lines and then start on the first quarter of the marked floor space.
 5. Keep a distance of 10mm from the wall and the edge of the flooring products. Press products down firmly so that the products lie flat on the ground.
 6. NFD recommends the random installation method and also recommends mixing 4-5 boxes to achieve a more natural appearance. Loose laying and re-shuffling before locking the hybrid together is the best way to obtain this.
 7. End joins row to row to be no less than 35cm.
 8. No plank should be cut smaller than one-third of its width or one-eighth of its length
-

Custom Stair Tread:

Stairs must be clean, dry and free from any debris suitable for bonding to. Stairs need to be square-edge and, therefore, the face may need to be packed.

Remove any cushion underlay backing from all products that are to be used on the stairs.

Custom stair treads must be fully adhered to the tread and face of the stair by using the timber insert. All products used on stairs must also be fully adhered. A suitable high temperature resistant adhesive must be used.

The top custom stair tread must also be fixed to the stair, and if the same product is used adjoining an expansion must be left with a T cover or any other suitable cover allowing for the correct expansion space.

Steam mops are not allowed and will void the warranty of this flooring.

To protect the floor from heat and fading due to direct sunlight, use window coverings. Tinting windows may also be necessary.

Ensure the floor surface temperature does not drop below 5°C or exceed 45°C and avoid exposing it to dramatic temperature change. A surface temperature change of more than 10°C within 2 hours is considered dramatic and can cause issues like joint peaking or gaps.

NFD

HEAD OFFICE

58 Blanck Street
Ormeau, QLD
Australia 4208

CALL US

Phone: (07) 3806 2666
8:30AM - 5:00PM AEST

EMAIL US

info@nfd.com.au